



Sixth Semester B.E. Degree Examination, Dec.2019/Jan.2020

Design and Drawing of RC Structures

Time: 4 hrs.

Max. Marks:100

Note:1. Answer any TWO full questions from PART-A and any ONE question from PART-B.**2. Use of IS 456, IS 3370 and SP16 are permitted.****PART - A****1** A two way slab for a hall of internal dimensions $3.5 \times 4.5\text{m}$ has the following details :

- i) Thickness of the of slab = 150mm
- ii) Wall thickness = 230mm
- iii) 10mm ϕ bar at 120mm C/C along short span
- iv) 8mm ϕ bar at 140mm C/C along long span
- v) 6mm ϕ bar at 120mm C/C along torsional steel
- vi) 8mm ϕ bar at 300mm C/C along edge strip
- vii) Grade of concrete and steel : M_{20} and Fe415

Draw to a suitable scale the following :

- a. Plan showing reinforcement detail : (08 Marks)
- b. C/S of slab at mid span along short span (06 Marks)
- c. C/S of slab at mid span along long span. (06 Marks)

2 A doglegged staircase has to be provided for a public building with the staircase room of internal dimensions $2.60 \times 5.0\text{m}$ supported on wall on either end. The following detail are given :

- i) Widths of tread = 250mm
- ii) Rise = 180mm
- iii) Floor height = 3.60m
- iv) Number of steps in each flight = 10
- v) Waist slab thickness = 160mm
- vi) Wall thickness = 230mm
- vii) Main reinforcement = 12mm ϕ ω 120 mm C/C
- viii) Distribution reinforcement = 12mm ϕ ω 120mm C/C
- ix) Grade of concrete and steel = M_{20} and Fe 415

Draw to a suitable scale the following :

- a. Plan of stair (06 Marks)
- b. Sectional elevation along first flight (07 Marks)
- c. Sectional elevation along second flight. (07 Marks)

3 An isolated column and footing has the following details.

- i) Dimension of column - (300 \times 300)mm
- ii) Height of column - 3m
- iii) Main reinforcement in column - 4 - 16mm ϕ
- iv) Lateral ties in column - 6mm ϕ ω 150mm C/C
- v) Size of footing - 1.20m \times 1.20m
- vi) Thickness of footing at face of column - 450mm
- vii) Thickness of footing at edges - 150mm
- viii) Dept of foundation below G.L - 1.20m
- ix) Main reinforcement of footing in both ways - 100mm ϕ ω 90mm C/C
- x) Grade of concrete and steel - M_{20} and Fe 415

Draw to a suitable scale, the following :

- a. Sectional plan of column and footing (06 Marks)
- b. Sectional elevation of column and footing (08 Marks)
- c. Prepare the bar bending schedule. (06 Marks)

PART – B

- 4 Design a cantilever retaining wall to retain earth for a height of 4m. The backfill is horizontal. The density of the soil is 18kN/m^3 . Safe bearing capacity of the soil 200 kN/m^2 . Take co-efficient of friction between concrete and soil as 0.6. Angle of internal friction is 30° . Use M_{20} concrete and Fe 415 steel. (40 Marks)
Draw the following to a suitable scale :
- C/S of retaining wall showing reinforcement details (10 Marks)
 - Longitudinal section of the stem showing curtailment (06 Marks)
 - Half plan of top and half plan of bottom of base slab. (04 Marks)
- 5 A single bay fixed portal frame has an effective span of 7m and an effective height of 4.2m spacing of the portal frame is 4.2m. consider a live load of 3kN/m^2 on the slab. Column size is $230\text{mm} \times 750\text{mm}$ shall be adopted. Design the portal frame considering M_{20} concrete and Fe 415 steel. SBC of soil is 130kN/m^2 . (40 Marks)
Draw to a suitable scale
- The sectional elevation of half the portal frame showing the detail of reinforcement is beam, column and footing. (12 Marks)
 - C/S of column (04 Marks)
 - Plan of footing. (04 Marks)

* * * * *