



CBCS SCHEME

15AU62

Sixth Semester B.E. Degree Examination, Aug./Sept. 2020 Heat and Mass Transfer

Time: 3 hrs.

Max. Marks: 80

- Note: 1. Answer any FIVE full questions, choosing ONE full question from each module.
2. Use of heat transfer data hand book is permitted.

Module-1

- 1 a. Explain the modes of heat transfer. (03 Marks)
- b. State the laws governing three basic modes of heat transfer. (05 Marks)
- c. Derive general 3 – dimensional heat conduction equation in Cartesian co-ordinates. (08 Marks)

OR

- 2 a. Derive an expression for the temperature distribution and the rate of heat transfer for a hollow cylinder. (08 Marks)
- b. A wall is constructed of several layers. The first layer consists of brick ($k = 0.66 \text{ w/m k}$), 25cm thick, the second layer 2.5cm thick mortar ($k = 0.7 \text{ w/m k}$), the third layer 10cm thick limestone ($k = 0.66 \text{ w/m k}$) and outer layer of 1.25cm thick plaster ($k = 0.7 \text{ w/m k}$). The heat transfer coefficients on interior and exterior of the wall fluid layers are $5.8 \text{ w/m}^2\text{k}$ and $11.6 \text{ w/m}^2\text{k}$ respectively.
Find :
 - i) Overall heat transfer coefficient
 - ii) Overall thermal resistance per m^2
 - iii) Rate of heat transfer per m^2 , if the interior of the room is at 26°C while outer air is at -7°C
 - iv) Temperature at the junction between mortar and limestone. (08 Marks)

Module-2

- 3 a. Obtain an expression for temperature distribution and heat flow through a rectangular fin, when the end of fin is insulated. (08 Marks)
- b. An electronic semiconductor device has a rating of 60mw. In order to keep its proper operation, the inside temperature should not exceed 70°C . The device can dissipate about 20mw of heat on its own when placed in an environment at 40°C with heat transfer coefficient of $12.5 \text{ W/m}^2 \text{ k}$. To avoid overheating of the device, it is proposed to install aluminium ($k = 190 \text{ W/m k}$) square fins 0.6mm side, 10mm long, to provide additional cooling. Find the number of fins required. Assume no heat loss from the tip of fins. (08 Marks)

OR

- 4 a. Explain the following with their significance
- Biot number
 - Fourier number
 - Thermal time constant. (06 Marks)
- b. In a quenching process, a copper plate 3mm thick is heated upto 400°C and then exposed to an ambient at 25°C, with the convection coefficient of 28w/m²k. Calculate the time required for the plate to reach the temperature of 50°C. Take thermo-physical properties as C = 380 J/kg k, P = 8800 kg/m³, k = 385 W/m-k. (06 Marks)
- c. An aluminium cylinder (k = 210 W/m k) 50mm in diameter and 10cm long is initially at uniform temperature of 200°C. Take h = 530 W/m²k. What is the temperature on centerline of the cylinder after one minute? (04 Marks)

Module-3

- 5 a. Explain the following :
- Velocity boundary layer
 - Thermal boundary layer. (04 Marks)
- b. Vertical door of a hot oven is 0.5m high and is maintained at 200°C. It is exposed to atmospheric air at 20°C. Find :
- Local heat transfer coefficient half way up the door
 - Average heat transfer coefficient for entire door
 - Thickness of free convection boundary layer at the top of the door. (12 Marks)

OR

- 6 a. A rectangular tube, 30mm × 50mm carries water at a rate of 2kg/s. Determine the length of tube required to heat water from 30°C to 50°C, if the wall temperature is maintained at 90°C. (08 Marks)
- b. In a long annulus (3.5cm ID and 5cm OD), the water is heated by maintaining the outer surface of inner tube at 60°C. The water enters at 20°C and leaves at 34°C. While its flow rate is 2 m/s. Estimate the heat transfer coefficient. (08 Marks)

Module-4

- 7 a. Derive an expression for LMTD of parallel flow heat exchanger. (08 Marks)
- b. A heat exchanger is required to cool 55,000 kg/h of alcohol from 66°C to 40°C using 40,000 kg/h of water entering at 5°C. Calculate :
- Exit temperature of water
 - Heat transfer rate
 - Surface area required for
 - Parallel flow type
 - Counter flow type of heat exchanger
- Take overall heat transfer coefficient $U = 580 \text{ w/m}^2 \text{ k}$
- $C_{P(\text{alcohol})} = 3760 \text{ J/kg k}$
- $C_{P(\text{water})} = 4180 \text{ J/kg k}$ (08 Marks)

OR

- 8 a. With neat sketch, explain the regions of pool boiling. (08 Marks)
- b. A steam condenser consists of a square array of 400 tubes ($N = 20$) each 6mm in diameter. The tubes are exposed to saturated steam at pressure of 0.15bar ($T_{\text{sat}} = 54^\circ\text{C}$). The tube surface is maintained at a temperature of 25°C . Calculate the condensation rate per unit length of the tubes. The tubes are arranged horizontal in vertical tier of 20 tubes. (08 Marks)

Module-5

- 9 a. Explain briefly the concept of a block body. (04 Marks)
- b. State :
- Kirchoff's law
 - Wien's displacement law
 - Planck's law. (06 Marks)
- c. A hot water radiator of overall dimensions $2 \times 1 \times 0.2\text{m}$ is used to heat the room at 18°C . The surface temperature of radiator is 60°C and its surface is black. The actual surface of the radiator is 2.5 times the area of its envelope for convection for which the convection coefficient is given by
- $$h_c = 1.3(\Delta T)^{1/3} \text{ W/m}^2\text{k}$$
- Calculate the rate of heat loss from the radiator by convection and radiation. (06 Marks)

OR

- 10 a. define the following :
- Solid angle
 - Irradiation
 - Radiosity
 - Radiation shape factor. (04 Marks)
- b. State and explain Fick's law of diffusion. (04 Marks)
- c. Calculate the following quantities for an industrial furnace (black-body) emitting radiation at 2650°C .
- Spectral emissive power at $\lambda = 1.2\mu\text{m}$
 - Wavelength at which the emissive power is maximum
 - Maximum spectral emissive power
 - Total emissive power
 - Total emissive power of the furnace, if it is treated as gray and diffuse body with an emissivity of 0.9. (08 Marks)
