

USN

17AE52

Fifth Semester B.E. Degree Examination, Jan./Feb. 2021 Introduction to Composite Materials

Time: 3 hrs.

Max. Marks: 100

Note: Answer any FIVE full questions, choosing ONE full question from each module.

Module-1

1 a. Define Composite Materials? How they are classified?

(08 Marks)

b. Differentiate thermoplastics and thermoset polymers.

(06 Marks)

c. List the advantages and drawbacks of composites.

(06 Marks)

OR

- 2 a. Explain the solid state processing of MMC's. Also mention the advantages and applications.
 (08 Marks)
 - Explain the process of liquid forging with neat sketch. (06 Marks)
 - c. List the applications of Al, Mg and Ti based MMC's.

(06 Marks)

Module-2

- a. With a neat sketch, explain the thermoset polymer processing of Hand-layup process with advantages and disadvantages. (10 Marks)
 - b. Explain the process of filament winding with neat diagram. Also mention the advantages, drawbacks and applications. (10 Marks)

OR

- a. Explain with neat diagram the blow moulding process. Mention the applications. (10 Marks)
 - b. Explain the post processing of cutting in composites. Mention the advantages and disadvantages. (10 Marks)

Module-3

- 5 a. Define the following with equations:
 - i) Volume fraction
 - ii) Mass fraction
 - iii) Density of a composite
 - viv) Void content.

(12 Marks)

b. Determine the transverse Young's modulus by strength of material approach.

(08 Marks)

OR

6 a. Determine the global and local stresses in an angle lamina.

(10 Marks)

- For a graphite/epoxy unidirectional lamina, find the following:
- i) Compliance matrix
- ii) Minor Poisson's ratio
- iii) Strain in the 1-2 coordinate system, if the applied stresses are:
- $\sigma_1 = 2MPa$, $\sigma_2 = -3MPa$, $\tau_{12} = 4MPa$

[Use $E_1 = 181$ GPa, $E_2 = 10.3$ GPa, $\gamma_{12} = 0.28$, $G_{12} = 7.17$ GPa].

(10 Marks)

Module-4

- 7 Explain the following failure theories with equations:
 - i) Tsai-Hill failure theory
 - ii) Tsai-Wu failure theory.

(20 Marks)

OR

B Determine the terms [A], [B] and [D] matrices for a [0/90°] laminate with the following properties of lamina.

 $E_1 = 140$ GPa

 $E_2 = 10$ GPa

 $G_{12} = 5GPa$

 $\mu_{12} = 0.3$ and

Thickness of ply is 0.125mm

(20 Marks)

Module-5

- 9 a. Define NDT testing. Explain any one NDT testing with neat diagram. (10 Marks)
 - b. Explain about tensile and ultrasonic testing.

(10 Marks)

OR

- Give the applications of composite materials in the following:
 - a. Aircrafts
 - b. Missiles
 - c. Automobile
 - d. Sports equipment
 - e. Marine.

(20 Marks)