

USN

18AE/AS63

Sixth Semester B.E. Degree Examination, Dec.2023/Jan.2024 Finite Element Method

Time: 3 hrs.

Max. Marks: 100

Note: Answer any FIVE full questions, choosing ONE full question from each module.

Module-1

a. Explain Rayleigh-Ritz method and Galerkin's method applied in FEM. (10 Marks)

b. For the spring shown in Fig Q1(b) determine the nodal displacement using principle of minimum potential energy.

OR

a. Derive the Relationship between the generalized coordinates and nodel displacements.

(10 Marks)

b. Explain the convergence requirements of shape functions.

(05 Marks)


c. Define shape function and explain the shape function of an element for different conditions.

(05 Marks)

Module-2

3 a. Derive the shape function for a 1-D Bar element in Global and local coordinates. (10 Marks)


b. Find nodal displacements, stress in the thickest section and left support reaction for structure shown in Fig Q3(b)



(10 Marks)

OR

a. Consider the three bar truss shown in Fig Q4(a). Determine the nodal displacement and stress in each member. Find the support reactions. Take $E = 2 \times 10^5 MPa$.



(12 Marks)

b. Obtain Hermite shape function for beam element.

(08 Marks)

Module-3

5 a. Derive shape function of a CST element in natural coordinate systems.

(10 Marks)

b. Derive stiffness matrix for A-noded Tetrahedral element.


(10 Marks)

OR

6 a. Derive shape function for nine noded rectangular elements.

(10 Marks)

b. Determine the Jocobian of the transformation J for the triangular element shown in Fig Q6(b)



Module-4

- 7 a. Draw the mapping of iso-parametric elements in global coordinate system and explain briefly. (10 Marks)
 - b. With a neat sketch, explain ISO, sub and super parametric elements.

(10 Marks)

(10 Marks)

OR

8 a. Explain the structure of computer program for FEM Analysis.

(10 Marks)

b. Explain briefly the axisymmetric formulation finite element modeling of triangular element.
(10 Marks)

Module-5

9 a. Find the temperature distribution and heat transfer through an iron fin of thickness 5mm, height = 50mm, and width 1000mm. The heat transfer coefficient around the fin is 10W/m² K and ambient temperature is 28°C. The base of fin is at 108°C. Take K = 50W/m.K. Use two elements.




Fig Q9(a) (12 Marks)

b. Derive the governing differentiate equation for 1-D heat conduction.

(08 Marks)

OR

10 a. Explain formulation of Hamilton's principle.

(08 Marks)

b. Discuss the element mass matrices for the following elements in detail

i) 1 – D bar element ii) Truss element

Truss element iii) CST element.

(12 Marks)