

# CBCS SCHEME

18CV43

USN

## Fourth Semester B.E. Degree Examination, Dec.2023/Jan.2024 Applied Hydraulics

Time: 3 hrs.

Max. Marks: 100

*Note: Answer any FIVE full questions, choosing ONE full question from each module.*

### Module-1

- 1 a. What is dimensional analysis? List the uses of dimensional analysis. (04 Marks)
- b. The pressure drop ' $\Delta P$ ' in a pipe of diameter  $D$  and length  $l$  depends on mass density  $\rho$  and viscosity  $\mu$  of the flowing fluid, mean velocity of flow  $V$  and average height  $K$  of roughness projections on the pipe surface. Obtain a dimensionless expression for  $\Delta P$ . Hence show that
- $$h_f = \frac{f l v^2}{2gD} \quad (10 \text{ Marks})$$
- c. Explain detail the stability of submerged and floating bodies. (06 Marks)

OR

- 2 a. A solid cylinder of diameter 4.0m has a height of 3metres. Find the meta centric height of the cylinder when it is floating in water with its axis vertical. The specific gravity of the cylinder = 0.6. (08 Marks)
- b. A 1:10 scale model of a submarine moving far below the surface of water is tested in a wind tunnel. If the speed of the prototype is 8m/sec, determine the corresponding velocity of water in the tunnel. Also determine the ratio of the drag for the model and prototype. Kinematic viscosity  $\gamma_{\text{seawater}} = 1.121 \times 10^{-6} \text{ m}^2/\text{sec}$ ,  $\gamma_{\text{water}} = 1 \times 10^{-6} \text{ m}^2/\text{sec}$ ,  $\rho_{\text{seawater}} = 1027\text{kg/m}^3$ ,  $\rho_{\text{water}} = 1000\text{kg/m}^3$ . (08 Marks)
- c. List and explain the selection of repeating variables in Buckingham's Pi theorem of dimensional analysis. (04 Marks)

### Module-2

- 3 a. What is a most economical channel section? With usual notations derive the conditions for a most economical trapezoidal channel section. (06 Marks)
- b. Explain briefly classification of flow in channel sections. (05 Marks)
- c. Water flows in a trapezoidal channel having bottom width 6m, side slopes 2 horizontal to 1 vertical. If it has to carry a discharge of  $65\text{m}^3/\text{sec}$ , compute the bottom slope required to be provided. Taking Mannings  $n = 0.025$ , depth of flow = 2m. (09 Marks)

OR

- 4 a. An irrigation channel of trapezoidal section, having side slopes 3 horizontal to 2 vertical is to carry a flow of  $10\text{m}^3/\text{sec}$  on a longitudinal slope of 1 in 5000. The channel is to be lined for which the value of friction coefficient in Mannings formula is  $n = 0.012$ . Find the dimensions of the most economic section of the channel. (09 Marks)
- b. Draw a neat specific energy curve in a flow in a channel section. Mark and explain the salient points in it. (06 Marks)
- c. Show that for flow in a rectangular channel section, at critical conditions  $y_c = \frac{2}{3}E$ , where  $y_c$  is the critical depth and  $E$  is the energy of flow at critical depth. (05 Marks)

**Module-3**

- 5 a. With usual notations derive an expression for hydraulic jump in rectangular channels in term of Froude's number. (09 Marks)
- b. The depth of flow of water, at a certain section of a rectangular channel of 2m width is 0.3m. The discharge through the channel is  $1.5\text{m}^3/\text{sec}$ . Determine whether a hydraulic jump will occur, and if so, find the height and loss of energy per kg of water. (06 Marks)
- c. Describe briefly the water curves for a mild and sleep slopes. (05 Marks)

OR

- 6 a. A rectangular channel 7.5m wide has a uniform depth of flow of 2m and has a bed slope of 1 in 3000. If due to weir constructed at the downstream end of the channels water surface at a section is raised by 0.75m, determine the water surface slope with respect to horizontal at this section. Assume Mannings  $n = 0.02$ . (08 Marks)
- b. With usual notations derive an expression for a length of back water curve, in a channel section. (06 Marks)
- c. Explain in brief different types of hydraulic jump. What are the applications of hydraulic jump? (06 Marks)

**Module-4**

- 7 a. Give a brief description of impulse momentum equation and what are the practical applications of impulse momentum equation. (04 Marks)
- b. With usual notations prove that the maximum efficiency of a jet striking a series of moving flat vanes fixed on the periphery of the wheel is 50%. (06 Marks)
- c. With a neat sketch, explain the general layout of a hydraulic power plants. Explain different types of efficiencies of hydro electric turbines. (10 Marks)

OR

- 8 a. Give a brief account on classification of turbines based on different criteria. (06 Marks)
- b. A Pelton wheel has to be designed for the following data. Power to be developed = 6000kW. Net head available = 300m, speed = 500rpm. Ratio of jet diameter to wheel diameter =  $\frac{1}{10}$  and overall efficiency = 85%. Find the number of jets, diameter of the jet, diameter of the wheel and quantity of water required. (08 Marks)
- c. With a neat diagram, explain different components of Pelton wheel. With the help of velocity triangle find the expression for efficiency of Pelton wheel. (06 Marks)

**Module-5**

- 9 a. Design a Francis turbine runner with the following data. Net head  $H = 68\text{m}$ , speed  $N = 750\text{ rpm}$ , output power  $P = 330\text{kW}$ ,  $\eta_h = 94\%$ ,  $\eta_0 = 85\%$ , flow ratio  $\psi = 0.15$ , breadth ratio  $n = 0.1$  inner diameter of runner is  $\left(\frac{1}{2}\right)$  outer diameter. Also assume 6% of circumferential area of the runner to be occupied by the thickness of the vanes. Velocity of flow remains constant throughout and flow is radial at exit. (08 Marks)
- b. Explain the functions of draft tube in reaction turbines. What are its different types explain with diagrams. (04 Marks)
- c. A Kaplan turbine develops 24647.6kW power at an average head of 39 metres. Assuming a speed ratio of 2, flow ratio of 0.6, diameter of the boss equal to 0.35 times the diameter of the runner and an overall efficiency of 90%, calculate the diameter, speed the turbine. (08 Marks)

OR

- 10 a. With neat diagram, explain the component and working of centrifugal pumps. (06 Marks)
- b. With a neat diagram, derive an expression for minimum starting speed of centrifugal pumps with usual notations. (04 Marks)
- c. A centrifugal pump is running at 1000rpm. The outer vane angle of the impeller is  $45^\circ$  and velocity of flow at outlet is 2.5m/sec. The discharge through the pump is 200 litres/sec. When the pump is working against a total head of 20m. If the manometric efficiency of the pump is 80% determine:
- The diameter of the impeller
  - The width of the impeller at outlet.
- (10 Marks)

\*\*\*\*\*